



	4-5 kW	6-9 kW	10 kW	12 kW	15-18 kW	20-25 kW	30 kW	33-36 kW
AC								
Disjoncteur	C10	C16	C20	C25	C32	C40	C50	C63
Différentiel	25A 30mA G		40A 300mA AC				63A 300mA AC	
Passages de câbles PE	2 PE M25/32 + M20 (Terre)							
Raccordement en câble souple	Vers onduleur : 5G6-5G16 ; Vers réseau : 5G6-5G16 ; Terre : 16 mm ²							
DC								
MPP	2						3	
String par MPP	2							
Inter sectionneur Un/In	1000V / 50A							
Entrées / Sorties	8xMC4 / 4xPE M16 + terre PE M16						12xMC4 / 6xPE M16 + terre PE M16	
Coffret (mm)	470x426x148 (2x18) 420x314x143 (2x12M) sans parafoudre						657x426x148 (3x18) 470x426x148 (2x18) sans parafoudre	
Codes avec parafoudre DC	2051105001	2091105001	2141105001	2121105001	2221105001	2281105001	2301105001	2361105001
Codes sans parafoudre DC	2051105002	2091105002	2141105002	2121105002	2221105002	2281105002	2301105002	2361105002



Figure 46 : Photo coffret AC+DC TRI 6-9 kW ref 209110501