



APbattery-51.2V/10.24kWh

- Max 32 Batteries in parallel, up to 327.68 kWh capacity
- Automatic Parallel Configuration
- Supports Charging Down to -5 °C
- Outdoor and Indoor Application (IP65)

Features



Easy installation



Slim & modern design



Advanced BMS control



Parallel capacity up to 327.68 kWh

<u>-j</u>

Black out and emergency back-up

=

Self-heating for low ambient temperatures

a

Remote monitoring with over-the-air updates

<u>_~</u>

Low voltage LiFePO₄ battery

Datasheet | APbattery-51.2V/10.24kWh

Model Region	APbattery-51.2V/10.24kWh EMEA
Rated Capacity	200 Ah
Rated Voltage	51.2 V
Rated Current	0.6C, 120 A
Working Voltage Range	43.2-58.4 V
Rated Energy	10.24 kWh
Usable Energy	9.22 kWh
Max. Parallel Quantity	Max. 32 Sets In Parallel , 327.68 kWh
Rated Charging Current	0.6C , 120 A
Rated Discharge Current	0.6C , 120 A
Battery Max. Charge/Discharge Power	6.14 kW/6.14 kW
Standard Charging Method	0.5C CC to 57.6 V; CV at 57.6 V Till Current Is 0.05C
Available SOC Range	0% ~ 100%
SOC Transportation Range	50%
Dimensions [W*D*H]	Width: 550(±5)mm/21.6 in Depth: 165(±5)mm/6.50 in Height: 867(±5)mm/31.21 in
Weight	94 kg
Operating Temperature ¹	Charging Temperature: 0°C~55°C or -5°C~55°C Discharge Temperature: -15°C-55°C
Storage Temperature ²	-15°C ~ 55°C
RTE	94%
DOD	90%
Working Humidity	<95% RH (non-condensing)
Altitude ³	≤2000 m
Communication	CAN, RS485, Dry Contact, Wi-Fi
PACK Safety Certifications	IEC 62619 / IEC 62040 / IEC 61000
Cell Safety Certifications	IEC62619 / UL1973
UN Transportation Test Standard	UN38.3
Designed Cycle Life (25°C±2°C)	6000 Cycles
IP Rating	IP65
Cooling	Natural Cooling
Heating Power	230.4 W
Warranty	10 Years Limited Warranty
Environment Protection Standard	RoHS
1. Recommended operating temperature: 10 ~ 30°C.	© All Rights Reserved

Specifications subject to change without notice please ensure you

are using the most recent update found at web : $\underline{\text{emea.APsystems.com}}$

APsystems EMEA

Karspeldreef 8, 1101 CJ, Amsterdam, The Netherlands Email: support.emea@Apsystems.com Web: emea.APsystems.com

22 Avenue Lionel Terray 69330 Jonage France Email: support.emea@Apsystems.com Web: emea.APsystems.com

^{2.} Recommended Storage temperature: 10 ~ 30°C.

^{3.} Recommended working height is less than 2000 m, and the max. working height is 3000 m.